



产品资讯

Product Information

NYLOY® GMG-0133B-2

- 尼龙 66
Nylon 66
- 玻纤强化
Glass Fiber Reinforced
- 黑色
Black

Lot.No. : F2A2260026

性质	PROPERTIES	测试方法 METHOD	单位 UNIT	结果(数据) RESULT
机械特性	MECHANICAL			
抗张强度	Tensile Strength	ASTM D638	kg/cm ² (MPa)	1450 (142)
断裂伸长率	Elongation	ASTM D638	%	2.5
抗折强度	Flexural Strength	ASTM D790	kg/cm ² (MPa)	2250 (220)
抗折弹性系数	Flexural Modulus	ASTM D790	kg/cm ² (MPa)	86000 (8425)
冲击强度	IZOD Impact, Notched 23° C	ASTM D256	kg-cm/cm (J/M)	10.0 (98)
	IZOD Impact, Notched -20°C	ASTM D256	kg-cm/cm (J/M)	-
硬度	Hardness Rockwell R Scale	ASTM D785	-	-
热特性	THERMAL			
热变形温度	Heat Deflection Temp	ASTM D648		
	264 psi		°C	-
其他特性	OTHER			
密度	Density	ASTM D792	g/cm ³	1.395
模收缩率	Mold Shrinkage	ASTM D955		
	横向	Normal, 2.0mm	%	-
	纵向	Parallel, 2.0mm	%	-
耐燃性	Flammability	UL-94	1.6mm	-
附注	REMARK			
(1)本物性表为典型测试值, 仅供参考, 不作为正式质保承诺。				

